

IP TELEPHONE APPARATUS AND IP TELEPHONE SYSTEM

BACKGROUND OF THE INVENTION

Field of the Invention

5 This invention relates to an IP telephone apparatus and an IP telephone system including an Internet telephone function in addition to a general telephone function provided through a public switched telephone network.

10 Background Art

 The Internet telephone means a telephone conversation mode in which a packet carrying a voice is transferred in a two-way manner via the Internet. A related art to the Internet telephone for enabling a user to use both the Internet telephone
15 and general telephone (ordinary telephone) functions (for example, refer to JP-A-10-155034) and the like are known.

 In the related art, the user can use both the Internet telephone and general telephone functions from the telephone main unit, but cannot use the Internet telephone function from
20 an external telephone including only the general telephone function. Particularly, the user who owns an apparatus for enabling the user to use the Internet telephone function and a telephone including only the general telephone function may want to also use the Internet telephone function at low
25 communication costs from the telephone including only the

general telephone function.

SUMMARY OF THE INVENTION

It is therefore an object of the invention to provide
5 an IP telephone apparatus and an IP telephone system for enabling
the user to conduct Internet telephone conversation even with
an external telephone having only a general telephone function.

To achieve the above object, the invention provide an
IP telephone apparatus, for executing a telephone call through
10 a computer network, including: a main unit having a handset;
a telephone line connection unit that connects to a telephone
network; an external telephone connection unit being
connectable to an external telephone having a handset; a dialing
start command detection unit configured to detect an IP telephone
15 dialing start command; an audio signal input/output unit that
inputs/outputs an audio signal for conversation when the dialing
start command unit detects an IP telephone dialing start command;
a handset validation unit configured to selectively validate
one of the handset of the main unit and the handset of the external
20 telephone; an audio signal path switching unit that switches
a connection target of the handset validated by the handset
validation unit from the telephone line connection unit to the
audio signal input/output unit when the dialing start command
detection unit detects the IP telephone dialing start command;
25 and a network communication control unit configured to enable

the audio signal input/output unit to transmit and receive the audio signal to and from the network terminal when the dialing start command detection unit detects the IP telephone dialing start command.

5 According to the IP telephone apparatus, the user can conduct Internet telephone conversation using the IP telephone apparatus alone and in addition, for example, if an external telephone such as a cordless telephone or an external installed telephone having only the general telephone function is
10 connected, the user can conduct Internet telephone conversation using the external telephone.

 The invention may provide an IP telephone system, including: a computer connected to a network terminal via a computer network; a handset that receives and generates an audio
15 signal for a telephone conversation; a telephone line connection unit connectable to a telephone network; a computer connection unit connectable to the computer; an audio signal path switching unit that switches a path of the audio signal to one of the telephone line connection unit and the computer connection unit;
20 an external telephone connection unit connected to an external telephone having a general telephone function for telecommunicating through a telephone network; and an IP telephone relay unit configured to receive a predetermined command from the external telephone through the external
25 telephone connection unit and to make the audio signal path

switching unit switch the path to the computer connection unit upon reception of a predetermined command, so that the external telephone can telecommunicate with the network terminal.

The invention may provide an IP telephone apparatus, for
5 executing a telephone call through a computer network,
including: a main unit having a handset; a telephone line
connection unit that connects to a telephone network; an external
telephone connection unit being connectable to an external
telephone for executing a telephone call through a telephone
10 network, the external telephone having a handset; a dialing
start command detection unit configured to detect an IP telephone
dialing start command; an audio signal input/output unit that
inputs/outputs an audio signal for conversation when the dialing
start command unit detects an IP telephone dialing start command;
15 a handset validation unit configured to selectively validates
one of the handset of the main unit and the handset of the external
telephone; an audio signal path switching unit that switches
a connection target of the handset validated by the handset
validation unit from the telephone line connection unit to the
20 audio signal input/output unit when the dialing start command
detection unit detects the IP telephone dialing start command;
and a network communication control unit configured to enable
the audio signal input/output unit to transmit and receive the
audio signal to and from the network terminal when the dialing
25 start command detection unit detects the IP telephone dialing

start command.

The invention may provide an IP telephone apparatus,
including: a main unit having a handset; an external
telephone connection unit being connectable to an external
5 telephone having a handset; a telephone line connection unit
being connectable to a telephone network; a network connection
unit being connectable to a computer network; an IP command
generating unit configured to generate an IP telephone command
for executing an IP telephone call; a handset validation unit
10 configured to selectively validate one of the handset of the
main unit and the handset of the external telephone; an audio
signal path switching unit that switches a connection target
of the handset validated by the handset validation unit from
the telephone line connection unit to the network connection
15 unit upon detection of the IP telephone command.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention may be more readily described with
reference to the accompanying drawings, in which:

20 FIG. 1 is a block diagram showing an IP telephone apparatus
according to the invention;

FIG. 2 is a flowchart showing a processing procedure of
the IP telephone apparatus for making a call (calling);

FIG. 3 is a schematic representation showing setup modes
25 for each machine;

FIG. 4 is a flowchart showing a processing procedure of the IP telephone apparatus upon reception of a call (incoming call) from an Internet telephone calling party;

FIG. 5 is a block diagram showing a modification of an IP telephone system;

FIG. 6 is a block diagram showing another modification of an IP telephone system; and

FIG. 7 is a block diagram of an external telephone in the IP telephone system shown in FIG. 6.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring now to the accompanying drawings, there is shown a preferred embodiment of the invention.

FIG. 1 is a block diagram showing an IP telephone system according to the embodiment.

As shown in FIG. 1, an IP telephone system 1 includes an IP telephone apparatus 10 having a function for conducting voice conversation based on an audio signal transmitted via a telephone network 100 and a personal computer (PC) 20 capable of conducting data communications via the Internet 200, the IP telephone apparatus 10 and the PC 20 being connected by an audio cable 300 capable of transmitting an audio signal and a USB (universal serial bus) cable 400 capable of transmitting a control signal.

The IP telephone apparatus 10 includes a control section

11 for controlling the whole operation of the apparatus, a record and playback section 12 for playing back a voice based on an audio signal and recording an audio signal, a user interface section (user I/F) 13, a handset 14 used in a state in which the handset is removed from the IP telephone apparatus 10 main unit, a voice input/output section 15 for inputting/outputting a voice, an external telephone connection section 16 for connecting an external telephone, an NCU (network control unit) 17 for inputting/outputting an audio signal transmitted via the telephone network 100, an external interface section 18 including an audio signal interface section (voice I/F) 18a for inputting/outputting an audio signal transmitted over the audio cable 300 and a control signal interface section (control I/F) 18b for inputting/outputting a control signal transmitted over the USB cable 400, a path switching section 19 for switching an audio signal transmission path in the IP telephone apparatus 10, a slave terminal 30 for conducting radio communications with the IP telephone apparatus 10 main unit (external telephone connection section 16), and the like.

The record and playback section 12 includes a message playback section 12a for playing back voice (sound) based on various audio signals previously recorded and a message record section 12b for recording a message recorded in an automatic answering mode as an audio signal. Recorded in the message playback section 12a are audio signals such as a ring tone used

upon reception of an incoming call, a holding tone used when voice conversation is held, and a telephone answering mode message telling that recording a message is started by an automatic answering mode function.

5 The user I/F 13 includes a plurality of operation keys 13a consisting of keys and a display panel 13b for displaying various pieces of information. The operation keys 13a include a plurality of numeric keys, a hold key for starting and

terminating holding of voice conversation, a switch key for

10 switching the transmission path used to input/output an audio

signal from/to the outside from the NCU 17 to the voice I/F 13, and

18a, an outside line key for starting voice conversation, and

off key for terminating voice conversation, and the like.

 The voice input/output section 15 includes a loudspeaker

15 15a, a microphone 15b, and a drive circuit 15c for driving the

loudspeaker 15a and the microphone 15b, and can be used not

only to output voice (sound) based on various audio signals

from the loudspeaker 15a, but also to conduct voice conversation

(hand-free conversation) with the loudspeaker 15a and the

20 microphone 15b as a handset.

 The external telephone connection section 16 includes

a radio communication section 16a for transmitting and receiving

various signals containing an audio signal by radio

communications with the slave terminal 30. The radio

25 communications are realized through the radio communications.

The external telephone connection section 16 further includes an external machine connection terminal 16b for connecting a mobile telephone (not shown), a different telephone apparatus (not shown), etc., by a cable. Wire communications are realized through the external machine connection terminal 16b with a mobile telephone, a different telephone apparatus, etc. The path switching section 19 switches the transmission path used to input/output an audio signal from/to the outside of the IP telephone apparatus 10 to either the NCU 17 or the voice I/F 18a in response to a command received from the control section 11. The transmission path is switched to the NCU 17 in the initial state.

If the user performs operation to start conversation (off-hook operation) with a component functioning as handset (any of the handset 14, the voice input/output section 15, or the slave terminal 30 (external telephone connection section 16), which will be hereinafter referred to as handset component), the path switching section 19 sets the transmission destination of an external input audio signal and the transmission source of an audio signal output to the outside to any handset component. Specifically, if the user removes the handset 14 from the IP telephone apparatus 10 main unit, the audio signal transmission destination and source are set to the handset 14; if the user presses the outside line key of the operation key 13a of the user I/F 13, the audio signal transmission destination and source

are set to the voice input/output section 15; if the user performs operation to start conversation with the slave terminal 30 (presses an outside line key forming a part of operation keys 33 described later), the audio signal transmission destination

5 and source are set to the external telephone connection section 16. On the other hand, if the user performs operation to terminate conversation (on-hook operation) with any handset component, the audio signal transmission destination and source set to any handset component are canceled. Specifically, when
10 the user restores the handset 14 to the IP telephone apparatus 10 main unit, presses the off key of the operation key 13a of the user I/F 13, or performs operation to terminate conversation with the slave terminal 30, the audio signal transmission destination and source are canceled.

15 The slave terminal 30 includes a control section 31 for controlling the whole operation of the slave terminal 30, a transmission-reception section 32 including a loudspeaker, a microphone, and a drive circuit for driving the loudspeaker and the microphone, a plurality of operation keys 33, a display
20 panel 34 for displaying various pieces of information, a playback section 35 for playing back voice (sound) based on various audio signals previously recorded, a loudspeaker section 36 including a loudspeaker and a drive circuit for driving the loudspeaker for outputting voice (sound) played back by the playback section
25 35, a radio communication section 37 for transmitting and

receiving various signals containing audio signals as radio signals to and from the radio communication section 16a of the IP telephone apparatus 10 main unit, and the like. The operation

5 keys 33 of the slave terminal 30 include a plurality of numeric keys, an outside line key for starting voice conversation, an off key for terminating voice conversation, a hold key for starting and terminating holding of voice conversation, and the like. Audio signals such as a ring tone used upon reception

of an incoming call and a holding tone used when voice conversation is held are recorded in the playback section 35.

The PC 20 includes a control section 21 for controlling the whole operation of the PC 20, a storage section 22 for storing

various pieces of information, a communication section 23 for connecting the PC 20 to the Internet 200, an external interface

15 section 24 including an audio signal interface section (voice I/F) 24a for inputting/outputting an audio signal over the audio cable 300 and a control signal interface section (control I/F)

24b for inputting/outputting a control signal over the USB cable 400, an operation section 25 including a keyboard, a mouse,

20 etc., a display 26, and the like.

The PC 20 has a function of realizing voice conversation based on an audio signal transmitted via the Internet 200, which will be hereinafter referred to as Internet conversation function. The Internet conversation function is a function

25 realized as the following conversation start processing,

transmission and reception processing, and conversation termination processing are executed in accordance with procedures indicated by application software stored in the storage section 22 (conversation software):

5 First, the conversation start processing is processing for establishing connection (logical communication channel connection) with a PC in which the same conversation software is built among PCs that can conduct data communications through the Internet 200, thereby starting data communications with
10 the PC. The conversation start processing is started when the associated PC is specified through the operation section 25 with the conversation software started. The conversation software continues to output a notification signal of a control signal for notifying that voice conversation is started, through
15 the control I/F 24b and the USB cable 400 to the IP telephone apparatus 10, until the conversation termination processing is performed and the voice conversation using the Internet communication function is terminated after the conversation start processing is performed and the voice conversation using
20 the Internet communication function is started.

 In the transmission and reception processing, data is generated in packet units based on an audio signal, transmitted via the communication section 23 and the Internet 200 to the PC with which connection is being established. An audio signal
25 is also generated on the basis of data in packet units transmitted

via the Internet 200 and the communication section 23 from the PC with which connection is being established. In the embodiment, data in packet units is generated based on an audio signal input from the IP telephone apparatus 10 via the audio cable 300 and the voice I/F 24a and is output to the Internet 200. The audio signal generated based on the data in packet units is output to the IP telephone apparatus 10 via the voice I/F 24a and the audio cable 300. The transmission and reception processing is executed repeatedly until the conversation termination processing is executed after the conversation start processing is executed, whereby voice conversation is realized between the IP telephone apparatus 10 connected to the PC 20 and the PC connected through the Internet 200.

The conversation termination processing is processing of releasing the connection with the PC with which the connection is being established (logical communication channel disconnection from the PC), thereby terminating the use of the Internet conversation function. The conversation termination processing is started when another PC is specified as an associated conversation party or the conversation software is quitted through the operation section 25. When the conversation software is quitted through the operation section 25, the conversation software transmits a release signal for notifying that the connection is released from the PC in which the conversation software is built to the PC with which the

connection is being established. Upon reception of the release signal, the PC 20 also executes the conversation termination processing.

Although not described in detail, a partial section of the communication channel from the communication section 23 of the PC 20 to the Internet 200 (section from user to telephone station) is also used as a telephone line for connecting the section from the NCU 17 of the IP telephone apparatus 10 to the telephone network 100. In the section, according to ADSL (asymmetric digital subscriber line) technology, an audio signal transmitted through the telephone network 100 and data transmitted through the Internet 200 are transmitted in a superposition manner.

The NCU 17 implements a telephone line connection unit for connecting to the telephone network. The external telephone connection section 16 implements an external telephone connection unit for connecting an external telephone having a handset. The control section 11 of the IP telephone apparatus 10 implements an IP dialing start command detection means for detecting an IP telephone dialing start command, a handset validation unit for selectively validating either of the handset of the apparatus main unit and the handset of an external telephone, and a network communication control unit for transmitting and receiving an audio signal to and from any other network terminal when an IP telephone dialing start command

is detected. The voice I/F 18a of the IP telephone apparatus
10 implements an audio signal input/output unit for
inputting/outputting an audio signal for conversation from/to
any other network terminal when the IP telephone dialing start
5 command detection unit detects an IP telephone dialing
conversation start command. The path switching section 19 of
the IP telephone apparatus 10 implements an audio signal path
switching unit that switches a connection target of the handset
validated by the handset validation unit from the telephone
10 line connection unit to the audio signal input/output unit.
The control I/F 18b of the IP telephone apparatus 10
implements a control signal input/output unit being connected
to computer to input/output various control signals containing
an IP telephone dialing start command. The control section
15 11 of the IP telephone apparatus 10 implements a message
transmission unit, upon reception of an off-hook signal from
an external telephone, for sending to the external telephone
a guidance message to selectively use either of the general
telephone and IP telephone functions for transferring an audio
20 signal via the telephone line connection unit. The control
section 11 also implements a mode setting unit for setting a
switch mode for enabling the user to selectively switch between
the general telephone and IP telephone functions for use or
a fixed mode for enabling the user to use only either telephone
25 function.

Further, the external interface section 18 of the IP telephone apparatus 10 implements a computer connection unit for inputting/outputting signals containing an audio signal transferred to and from any other terminal on the Internet from/to computer connected to the Internet. The control section 11 of the IP telephone apparatus 10 implements an Internet telephone relay unit, upon reception of a predetermined command from an external telephone through the external telephone connection unit, for switching the audio signal path switching unit into a state in which transfer of an audio signal using the IP telephone function can be executed between any other terminal on the Internet and the external telephone. The control section 11 implements a mode setting unit for setting an all calling mode for sending a ringing signal to the external telephone in response to a connection request received from each of a calling party on the telephone network and any other terminal on the Internet or a one calling mode for sending a ringing signal to the external telephone only when a connection request is received from either a calling party on the telephone network or any other terminal on the Internet.

Next, the main operation will be discussed with reference to the accompanying drawings.

FIG. 2 is a flowchart to show a processing procedure of the IP telephone apparatus 10 for making a call (calling). The operation keys 13a of the IP telephone apparatus 10 includes

a mode setting key for the user to set a switch mode for enabling the user to selectively use either of the general telephone and Internet telephone functions or an Internet telephone fixed mode or a general telephone fixed mode for enabling the user
5 to use only either of the general telephone and Internet telephone functions by mobile telephone (not shown) connected to the slave terminal 30 or the external machine connection terminal 16b.

To begin with, to make a call by performing the off-hook operation of the handset 14, etc., (YES at S1), the control section 11 of the IP telephone apparatus 10 validates the handset 14 and connects the handset 14 to the path switching section 19 (S2).

On the other hand, to make a call by performing the off-hook operation of the slave terminal 30, etc., (NO at S1 and YES at S3), the control section 11 recognizes the number of the slave terminal 30 (S4), validates the slave terminal 30, and connects the slave terminal 30 to the path switching section 19 (S5).

20 To make a call by performing the off-hook operation of the external telephone connected to the external machine connection terminal 16b, etc., (NO at S3), the control section 11 validates the external telephone and connects the external connected telephone to the path switching section 19 (S6).

25 A setup mode table for defining the use mode for each

machine is previously stored in a register, etc., of the control section 11, as shown in FIG. 3. The control section 11 references the setup mode table and performs the following processing:

If the setup mode of the validated machine is the switch mode (switch mode at S7), the control section 11 sends a guidance message to the validated machine for requesting the user to select an Internet telephone function or a general telephone function (S8). Thus, for example, the guidance message is displayed on the display panel 34 of the slave terminal 30 or is output by voice from the loudspeaker section 36. Of course, at the same time, the guidance message may be displayed or output by voice on the IP telephone apparatus 10. In this connection, the guidance message is, for example, a message telling that "only when calling an IP telephone call, dial "#" and then the telephone number." Entering "#" leads to an Internet telephone selection command.

Then, for example, the called party telephone number is entered on the slave terminal 30 and a DTMF (dual tone multifrequency) signal responsive to the entry operation is sent from the slave terminal 30 to the IP telephone apparatus 10. Upon detection of the DTMF signal from the slave terminal 30 (YES at S9), the control section 11 determines whether or not the DTMF signal contains an Internet telephone selection command (S10).

If the DTMF signal contains an Internet telephone

selection command (YES at S10), the control section 11 performs Internet telephone connection relay processing (S11). According to the Internet telephone connection relay processing, the IP telephone apparatus 10 is connected through the PC 20 to the Internet 200 and the called telephone terminal on the Internet 200 is accessed. When the called telephone terminal is placed in an off-hook state accordingly, a voice packet is transferred through the Internet 200. The voice packet is processed by the communication section 23 of the PC 20 at extremely high speed and as audio signal, is transferred between the IP telephone apparatus 10 and the PC 20 through the voice I/F 24a, the voice I/F 18a, and the audio cable 300. Further, voice is input/output between the IP telephone apparatus 10 and the radio communication section 37 of the slave terminal 30 through the voice I/F 18a, the path switching section 19, and the radio communication section 16a. Accordingly, Internet telephone conversation is conducted using the slave terminal 30. Similar operation is also performed in the external connected telephone. Of course, when an Internet telephone call is made from the IP telephone apparatus 10 as the main unit, an audio signal is transferred through the voice I/F 18a, the path switching section 19, and the handset 14 and thus to use the handset 14 of the main unit, the user can also conduct Internet telephone conversation.

For example, when Internet telephone conversation using

the slave terminal 30 is terminated and if an on-hook signal is received from the slave terminal 30 (YES at S12), the control section 11 performs Internet telephone disconnection processing (S13) and terminates the telephone calling relay processing. According to the Internet telephone disconnection processing, the connection state of the voice I/F 18a, the path switching section 19, the radio communication section 16a, and the like is released and the state is returned to the former standby state.

At S12, for example; if an on-hook signal is still unsent from the slave terminal 30 in the conversation state (NO at S12), the control section 11 continues the Internet telephone conversation state until reception of an on-hook signal.

If the DTMF signal does not contain an Internet telephone selection command (NO at S10), the control section 11 performs general telephone connection relay processing (S14). According to the general telephone connection relay processing, the IP telephone apparatus 10 is connected through the NCU 17, etc., to the telephone network 100 and the called telephone terminal on the telephone network 100 is called. When the called telephone terminal is placed in an off-hook state in response to the calling, an audio signal is transferred via the telephone network 100. The audio signal is transferred through the NCU 17, the path switching section 19, the radio communication section 16a, etc. Accordingly, general telephone conversation

is conducted using the slave terminal 30. When a general telephone call is made from the external connected telephone, an audio signal is transferred through the NCU 17, the path switching section 19, and the external machine connection terminal 16b, and general telephone conversation can also be
5 conducted with the external connected telephone. Of course, when a general telephone call is made from the IP telephone apparatus 10 as the main unit, an audio signal is transferred through the NCU 17, the path switching section 19, and the handset
10 14 and thus general telephone conversation can also be conducted with the main unit.

For example, if general telephone conversation using the slave terminal 30 is terminated and an on-hook signal is received from the slave terminal 30 (YES at S15); the control section
15 11 performs general telephone disconnection processing (S16) and terminates the telephone calling relay processing. According to the general telephone disconnection processing, the connection state of the NCU 17, the path switching section 19, the radio communication section 16a, and the like is released
20 and the state is returned to the former standby state.

If the DTMF signal from the slave terminal 30 cannot be detected (NO at S9), the control section 11 waits for the next processing until detection of the DTMF signal. When the DTMF signal cannot be detected although a predetermined time has
25 elapsed, the telephone calling relay processing may be

terminated as time-out processing.

If the setup mode of the validated machine is the Internet telephone fixed mode (Internet telephone fixed mode at S7), the control section 11 sends a message to the effect that the Internet telephone fixed mode is set to the validated machine (S20). In this case, unlike the switch mode, it is not necessary to enter prefix "#" to the called party telephone number.

Then, if the control section 11 detects the DTMF signal from the slave terminal 30 (YES at S21), for example, as the called party telephone number is entered on the validated slave terminal 30, the control section 11 goes to S11. On the other hand, if the DTMF signal from the slave terminal 30 cannot be detected (NO at S21), the control section 11 waits for the next processing until detection of the DTMF signal. When the DTMF signal cannot be detected although a predetermined time has elapsed, the telephone calling relay processing may be terminated as time-out processing.

Further, if the setup mode of the validated machine is the general telephone fixed mode (general telephone fixed mode at S7), the control section 11 sends a message to the effect that the general telephone fixed mode is set to the validated machine (S30).

Then, if the control section 11 detects the DTMF signal from the slave terminal 30 (YES at S31), for example, as the called party telephone number is entered on the validated slave

terminal 30, the control section 11 goes to S14. On the other hand, if the DTMF signal from the slave terminal 30 cannot be detected (NO at S31), the control section 11 waits for the next processing until detection of the DTMF signal. When the DTMF
5 signal cannot be detected although a predetermined time has elapsed, the telephone calling relay processing may be terminated as time-out processing.

Next, FIG. 4 is a flowchart to show a processing procedure

of the IP telephone apparatus 10 upon reception of a call
10 (incoming call) from an Internet telephone calling party. The operation keys 13a of the IP telephone apparatus 10 includes a mode setting key for the user to set an all calling mode for sending a ringing signal to the external connected telephone
and the slave terminal 30 when a connection request is received
15 regardless of whether the telephone calling party is general telephone or Internet telephone, or an Internet telephone only calling mode or a general telephone only calling mode for sending a ringing signal to the external connected telephone and the slave terminal 30 only if a connection request is received from
20 either of the telephone calling parties of general telephone and Internet telephone. In this connection, FIG. 4 shows a procedure for handling calling with the slave terminal 30; however, the procedure also covers handling of calling as the user performs off-hook operation of the external connected
25 telephone, the handset 14, etc.

To begin with, if an Internet telephone connection request is received via the PC 20 from a telephone calling party on the Internet 200 (YES at S40), the control section 11 makes a ring tone on the IP telephone apparatus 10 to inform the user
5 that an IP telephone call is being made (S41).

At the same time, the control section 11 checks which calling mode is set in the relationship between the IP telephone apparatus 10 as the main unit and the slave terminal 30 (S42). A setup mode table to be referenced at this time is also previously
10 stored in a register, etc., of the control section 11 although the table is not shown.

If the all calling mode or the Internet telephone only calling mode is set (YES at S42), the control section 11 sends a ringing signal to the slave terminal 30 (S43). Accordingly,
15 a ring tone is made on the slave terminal 30 in response to reception of the ringing signal.

Then, if an off-hook signal is received from the slave terminal 30 (YES at S45) before a predetermined time has elapsed (NO at S44), the control section 11 performs Internet telephone
20 connection relay processing (S46). According to the Internet telephone connection relay processing, the slave terminal 30 is connected through the PC 20 and the IP telephone apparatus 10 to the calling telephone terminal on the Internet 200, and a voice packet is transferred through the Internet 200. The
25 voice packet is processed by the communication section 23 of

the PC 20 at extremely high speed and is transferred as audio signal between the IP telephone apparatus 10 and the PC 20 through the voice I/F 24a, the voice I/F 18a, and the audio cable 300. Further, voice is input/output between the IP telephone apparatus 10 and the radio communication section 37 of the slave terminal 30 through the voice I/F 18a, the path switching section 19, and the radio communication section 16a. Accordingly, the Internet telephone call can be received using the slave terminal 30. Similar operation is also performed in the external connected telephone. Of course, if the user performs the off-hook operation of the handset 14 of the IP telephone apparatus 10 as the main unit, an audio signal is transferred through the voice I/F 18a, the path switching section 19, and the handset 14 and thus to use the handset 14 of the main unit, the user can also conduct Internet telephone conversation.

If Internet telephone conversation is terminated through the slave terminal 30 and an on-hook signal is received from the slave terminal 30 (YES at S47), the control section 11 performs Internet telephone disconnection processing (S48) and terminates the incoming call relay processing. According to the Internet telephone disconnection processing, the connection state of the voice I/F 18a, the path switching section 19, the radio communication section 16a, and the like is released and the state is returned to the former standby state.

At S47, if an on-hook signal is still unsent from the

slave terminal 30 (NO at S47), the control section 11 continues the Internet telephone conversation state until reception of an on-hook signal.

5 If an off-hook signal is not received from the slave terminal 30 (NO at S45), the control section 11 returns to S44.

If a predetermined time has elapsed without receiving an off-hook signal from the slave terminal 30 (YES at S44), the incoming call relay processing is terminated as time-out processing.

10 If the general telephone only calling mode is set (NO at S42), the control section 11 does not send a ringing signal to the slave terminal 30 and terminates the incoming call relay processing if an Internet telephone connection request is received. That is, in this case, no ring tone is made on the slave terminal 30.

If an Internet telephone connection request is not received (NO at S40), the control section 11 continues the standby state until reception of an Internet telephone connection request. If a general telephone connection request is received, a processing procedure responsive to the connection request is executed.

Therefore, according to the embodiment, the user can not only conduct Internet telephone conversation using the handset 14 of the IP telephone apparatus 10, but also make an Internet telephone call and conduct conversation using the slave terminal

30 including only the general telephone function.

To make an Internet or general telephone call using the slave terminal 30, when the slave terminal 30 is set to the switch mode on the IP telephone apparatus 10, a guidance message
5 for requesting the user to select either of the Internet telephone and general telephone functions is sent to the slave terminal 30 or the external connected telephone. Thus, the user can easily make an Internet or general telephone call simply by operating the slave terminal 30 according to the guidance
10 message.

An Internet telephone incoming call can be handled not only using the IP telephone apparatus 10, but also using the slave terminal 30.

If a connection request is received from an Internet
15 telephone calling party, a ringing signal is sent to the slave terminal 30, so that a ring tone is also made on the slave terminal 30, enabling the user to reliably know reception of an Internet telephone call.

The invention is not limited to the above-described
20 embodiment.

In the embodiment, the IP telephone system 1 includes the IP telephone apparatus 10 and the PC 20 connected by the audio cable 300 by way of example. However, if the IP telephone apparatus 10 has a configuration functioning in a similar manner
25 to that of the PC 20, only the IP telephone apparatus 10 may

implement the IP telephone system 1. Specifically, like an IP telephone system 2 shown in FIG. 5, the IP telephone apparatus 10 may additionally include a communication section 42 for connecting the IP telephone apparatus 10 to the Internet 200 and an Internet conversation processing section 44 in which conversation software is built for causing the control section 11 to function like the control section 21 of the PC 20 operating in accordance with the conversation software.

FIG. 6 shows an IP telephone system according to another embodiment of the invention. The IP telephone system 50 shown in FIG. 6 includes the IP telephone apparatus 10 and the computer 20, both configured the same as the IP telephone apparatus 10 and the computer 20 in the above embodiment. The IP telephone system 50 further includes an external telephone 60 connected to the external machine connection terminal 16b of the IP telephone apparatus 10.

FIG. 7 is a block diagram showing the configuration of the external telephone 60. The external telephone 60 is configured to exclusively execute a telephone call via a telephone network, and includes a control section 111 for controlling the whole operation of the apparatus, a record and playback section 112 for playing back a voice based on an audio signal and recording an audio signal, a user interface section (user I/F) 113, a handset 114 used in a state in which the handset 114 is removed from the external telephone 60 main unit, a voice

input/output section 115 for inputting/outputting a voice, an external telephone connection section 116 for connecting an external telephone, an NCU (network control unit) 117 for inputting/outputting an audio signal, and the like.

5 The record and playback section 112 includes a message playback section 112a for playing back voice (sound) based on various audio signals previously recorded and a message record section 112b for recording a message recorded in an automatic answering mode as an audio signal. Recorded in the message
10 playback section 112a are audio signals such as a ring tone used upon reception of an incoming call, a holding tone used when voice conversation is held, and a telephone answering mode message telling that recording a message is started by an automatic answering mode function.

15 The user I/F 113 includes a plurality of operation keys 113a consisting of keys and a display panel 113b for displaying various pieces of information. The operation keys 113a includes a plurality of numeric keys, a hold key for starting and terminating holding of voice conversation, an outside line
20 key for starting voice conversation, an off key for terminating voice conversation, and the like.

The NCU 117 is connected to the external machine connection terminal 16b of the IP telephone apparatus 10.

In the IP telephone system 50 shown in FIGs. 6 and 7,
25 the procedures of calling and an incoming call can be performed

are the same as the procedures shown in the flowchart of FIGs.
2 and 4.

According to the embodiment, the user can not only conduct
Internet telephone conversation using the handset 14 of the
5 IP telephone apparatus 10, but also make an Internet telephone
call and conduct conversation using the external telephone 60
including only the general telephone function.

To make an Internet or general telephone call using the
external telephone 60, when the external telephone 60 is set
10 to the switch mode on the IP telephone apparatus 10, a guidance
message for requesting the user to select either of the Internet
telephone and general telephone functions is sent to the external
telephone 60. Thus, the user can easily make an Internet or
general telephone call simply by operating the external
15 telephone 60 according to the guidance message.

Further, in the IP telephone system 50, an Internet
telephone incoming call can be handled not only using the IP
telephone apparatus 10, but also using the external connected
telephone 60.

20 Incidentally, the external telephone 60 may be connected
to the IP telephone apparatus 10 via the radio communication
section 16a by means of radio communications.

Incidentally, in the above embodiment, an automatic
answering function may be contained only in the external
25 telephone 60 and not contained in the IP telephone apparatus

10. In this case, the external telephone 60 can automatically respond to an Internet telephone incoming call and can record voice from the Internet telephone calling party. That is, simply by connecting to the IP telephone apparatus 10 an already
5 existing external telephone having only the general telephone function such as the external telephone 60, the Internet telephone function can be used and moreover effective use of various functions of the already existing external connected telephone can be made in Internet telephone.

10 Incidentally, in the above embodiments, it is necessary to prefix "#" to the called party telephone number in entering the telephone number when making an Internet telephone call; however, it may also be made necessary to enter a specific key when making a general telephone call.

15 As described above, according to the invention, the user can conduct Internet telephone conversation using the IP telephone apparatus alone and in addition, for example, if an external telephone such as a cordless telephone or an external installed telephone having only the general telephone function
20 is connected, the user can conduct Internet telephone conversation using the external telephone.

According to the invention, the user can conduct Internet telephone conversation via the computer connected to the Internet.

25 According to the invention, the user can conduct Internet

telephone conversation using a cordless telephone such as a slave.

According to the invention, the user can conduct Internet telephone conversation using a mobile telephone connected to the external machine connection terminal by a cable or the like.

According to the invention, the Internet telephone conversation start can be detected in response to the presence or absence of an Internet telephone command.

According to the invention, the user can conduct Internet telephone conversation using the handset of the apparatus main unit or the handset of the external telephone, which is off-hook at present.

According to the invention, when making an Internet or general telephone call using the external telephone, a guidance message for requesting the user to select either of the Internet telephone and general telephone functions is sent to the external telephone. Thus, the user can easily make an Internet or general telephone call simply by operating the external telephone according to the guidance message.

According to the invention, when making an Internet or general telephone call using the external telephone, a message responsive to the switch mode or the fixed mode set at the point in time is sent to the external telephone. Thus, the user can easily make an Internet or general telephone call simply by operating the external telephone according to the message.

According to the invention, the Internet telephone function is provided through the computer.

According to the invention, when a connection request is received from an Internet telephone calling party, the
5 external telephone can also handle the connection request.

According to the invention, when a connection request is received from an Internet telephone calling party, a ringing signal is sent to the external telephone, so that a ring tone
is also made on the external telephone, enabling the user to
10 reliably know reception of an Internet telephone call.

According to the invention, in the one calling mode for
sending a ringing signal to the external telephone only when
a connection request is received from a calling party on the
Internet, a ring tone is made on the external telephone only
15 when an Internet telephone call is received, enabling the user
to reliably know reception of the Internet telephone call.